

# Mid-Height Wall Collection

## COVENTRY® WALL III



“For many years, I’ve thought that I wanted my yard to be better.”



Scan the code to learn how EP Henry products and a creative contractor's solution salvaged this couple's backyard.

6" Coventry Wall III and Caps Pewter Blend; Bristol Stone I & II Pewter Blend; Cast Stone Wall Round Fire Pit Kit Cut Stone Adirondack



Dakota Blend



Pewter Blend

ENLARGED SWATCHES ON PAGE 87.  
SEE PAGE 64 FOR CAP OPTIONS.

Coventry Wall III is a versatile wall system, suitable for both Free-Standing & Single-Sided Wall applications.

All units are 6" high.



6" HIGH CUBE	A	B	C
SIZE (LxD)	8/6" x 10"	10/8" x 10"	16/14" x 10"
SF PER CUBE	32		
PCS PER CUBE	6" = 72		
LBS PER CUBE	6" = 3,223		

CAN BE USED IN SINGLE SIDED OR DOUBLE SIDED WALL APPLICATIONS



DOUBLE SIDED CORNER	6"
SIZE (LxD)	16" x 10"
PCS PER SF	1.5
SF PER CUBE	40
PCS PER CUBE	60
LBS PER PIECE	74
LBS PER CUBE	4,426



SINGLE SIDED CORNER	6"
SIZE (LxD)	14" x 8"
PCS PER SF	1.7
SF PER CUBE	44
PCS PER CUBE	75
LBS PER PIECE	51
LBS PER CUBE	3,829



BASE BLOCK	
SIZE (LxD)	18/17" X 10"
PCS PER CUBE	45
LF PER CUBE	67.5
LBS PER CUBE	3,870

### NOTES

- Maximum unreinforced wall height is 33"
- Coventry Wall III comes with splittable units to create corners: One 16" unit per layer is solid with no channels.
- Two pins/block needed (except under cap)
- For Coventry Wall III, the tightest radius possible using only the 10" and 6" long units is 33½". Using all sizes, the tightest possible radius is 48" to the back of the block