






Designed for steep, sloping hillsides and other structural challenges, the Vertica® retaining wall system can be built to virtually any height in incredibly tight spaces – thanks to an impressive 2-degree batter, built-in lug locators, and a nearly vertical rise for less excavation and land loss. Typically used with geosynthetic reinforcement, Vertica blocks meet or exceed industry standards for strength and durability.

- Evaluated by the Highway Innovative Technology Evaluation Center (HITEC) in the United States and the British Board of Agrément in the United Kingdom and is in compliance with the American Association of State Highway and Transportation Officials (AASHTO) and Federal Highway Administration (FHWA) design and construction standards
- Pinless, patented locator lug gives quick, uniform setback for reduced labor costs
- Used in commercial-site development or anywhere space is at a premium
- Features warm earth-tone colors and rugged,rock-like texture
- Can be used to build gravity walls up to 3 feet 4 inches high, including buried course, but excluding the cap*
- Taller walls can be built using geosynthetic reinforcement or the Anchorplex[™] retaining wall system when designed by a qualified engineer
- Minimum outside radius, measured on the top course to the front of the units: 5 feet
- Minimum inside radius, measured on the base course to the front of the units: 7 feet





Vertica® RETAINING WALL SYSTEM











Stretcher Units	Straight Face	Beveled Face	
Approximate Dimensions*	8" x 18" x 11"	8" x 18" x 11"	
Approximate Weight*	81 lbs.	78 lbs.	
Coverage	1.00 sq. ft.	1.00 sq. ft.	
Setback/System Batter	⁹ / ₃₂ "/2°	⁹ / ₃₂ "/2°	
Detbacky System Batter	/ 52 / 2	7 32 7 2	

Accessory Units	Cap	Corner
Approximate Dimensions*	Front, 4" x 17 ¹ / ₄ " x 10 ³ / ₈ " Back, 4" x 12" x 10 ³ / ₈ "	8" x 18" x 9" 8" x 18" x 9"
Approximate Weight*	41 lbs.	101 lbs.
Coverage	1.22 lin. ft.	1.50 sq. ft.

73.3005.2 08/15 4015



Visit anchorwall.com for installation instructions.

*Product dimensions are height by face length by depth. Actual dimensions and weights may vary from these approximate values due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

© 2015 Anchor Wall Systems, Inc. The logos, slogans, product names and other trademarks shown in this document are trademarks of Anchor Wall Systems, Inc. The wall system is made and sold under license from Anchor Wall Systems, Inc. (AWS). The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345.

