CLEANING PRODUCTS


EP Henry offers a complete line of cleaners from Techniseal to maintain the beauty of your pavers.

PROFESSIONAL GRADE OIL & GREASE REMOVER

 Dislodges set petroleum-based products, motor and hydraulic oil

PAVER PREP/EFFLORESCENCE CLEANER

- Dislodges efflorescence and ground-in dirt
- Ensures even cleaning and brightens the color
- · Automatic dilution with adaptable sprayer*
- Recommended PRIOR TO PROTECTOR application
- * Sprayer available through EP Henry Authorized Hardscaping Distributor®





PAVERS WITH EFFLORESCENCE

CLEANED PAVERS

PAINT, TAR, AND RUBBER REMOVER

- Effectively dissolves paint, tar or bitumen, rubber, and chewing gum
- Also available in five gallon containers to remove sealers

RUST REMOVER

- Effectively removes stains caused by steel, rusted metal objects, fertilizer, etc.
- · Won't discolor pavers

ORGANIC STAIN REMOVER

 Effectively removes moss, mildew, wine, blood, dead leaves and non-greasy food stains

DIRT & GREASE CLEANER

- · Removes motor oil and grease
- · Dissolves, dislodges and encapsulates grease

PAVER RESTORER

· Removes haze created by some polymeric sands

ECO-STRIPPER

 Removes most stains, sealants and coatings without affecting the surface

SEALERS

Sealing is recommended to preserve the original beauty of EP Henry Pavers and to resist stains. EP Henry is pleased to carry the Techni-Seal® line of high performance sealers, offering several options for protecting and maintaining the beauty of your EP Henry Pavers. Dirt, stains, and efflorescence must be treated with the appropriate Techni-Seal cleaning product prior to sealing.

"NATURAL LOOK"- MATTE FINISH (IN)

- · Preserves the natural look
- · Ideal for slip-prone surfaces

"SATIN LOOK"- SATIN FINISH (EV/JS)

- · Enhances the color of pavers
- · Stabilizers sand or aggregate joints

"COLOR BOOST"- MATTE FINISH (CB)

- Color Enhancement
- Ideal for slip-prone surfaces

"WET LOOK"- GLOSS FINISH (WLS/JSW)

- · Enhances the color of pavers
- · Stabilizers sand or aggregate joints

TECHNISEAL® RG ADHESIVE

Perfectly resist the elements including frost and rain, super-adherent on dry, wet, or frozen surfaces; ideal for retaining walls.

PAVER EDGE RESTRAINT

The purpose of Edge Restraint products is to restrain paver's lateral motion. Without a proper Edge Restraint System, pavers are prone to shifting. EP Henry offers the Snap Edge Paver Restraint System.

Note: See diagram of typical installation on page 2.



ADVANTAGES OF THE SNAP EDGE RESTRAINT SYSTEM:

- One piece system does it all; straight, curves, or even a complete radius, without waste
- An 8' piece transports easily and requires no extra connectors
- Open base design allows for grass growth along paver edge creating a strong yet invisible edge
- Patented snap and spike together ends for a secure connection and extra support
- Rugged injection molded plastic ensures the strongest edge designed for vehicular and patio/ walkway applications
- Can be installed before or after the pavers have been laid
- Easy to install with common 8"-12" landscape spike
- Convenient and efficient packaging, easy to handle.

SAND STABILIZERS

TECHNI-SEAL POLYMERIC SANDS

Techni-Seal offers two high quality Polymeric Sand products for pavement joints. Both resist erosion of joints, inhibit weed growth, and resist insect penetration. They are available in three colors: Tan, Urban Gray (Carbon) and Granite (Gray).

HP NEXT GEL JOINTING SAND

Techni-Seal now offers Next Gel, designed for wider joint applications and areas with heavy slopes, high traffic areas and high humidity.

The revolutionary technology behind Next Gel provides these benefits:

- No dust, haze or waste
- False or wide joints from 1/16" to 4"
- 50% faster wetting & 40% faster installation

SMARTSAND® with Next Gel Technology

Cost-effective alternative to HP Next Gel, when a high-performance sand is not required. Its "quick activation" formula makes it ideal for everyday installations, such as residential driveways, patios and walkways.

- Easy Sweep and no haze
- Pedestrian and low-traffic areas
- Paver joints from 1/16" to 1"





SEPARATION FABRIC

Mirafi ® 500x geotextile fabric is recommended for use with all paver installations. Its primary purpose is to keep the base material from working its way into the soil underneath, thus reducing the possibility of settling.

The material should be flat over the excavated area, with as few wrinkles as possible, and turned up on the sides to cover the sides of the stone base material. It will also prevent migration of the bedding sand into cracks, joints, and weep holes in or next to the pavement.

This product, which costs only pennies per square foot, is an inexpensive insurance policy for your payement.

Note: See diagram of typical installation on page 2.



Polymeric Sand must be installed per the manufacturer's guidelines. The user should have an up-to-date Techni-Seal technical product data sheet and should view the video of the RG+ installation procedure at: www.techniseal.com. The misapplication of Techni-Seal Polymeric Sand could generate a polymeric haze on the surface.

Techni-Seal Polymeric Sand must NOT be applied to wet or damp surfaces. Do NOT mix Techni-Seal Polymeric Sand with cement, sand or any other chemicals. Do NOT use on submerged or constantly wet surfaces. Use on pavers or slabs installed over a free draining sand-setting bed and compacted dense aggregate base as ICPI recommends. It is not recommended for use on concrete overlay construction or stone dust

A NOTE ABOUT PAVER ACCESSORIES

EP Henry has researched many lines of accessory products for use with our pavers and wall systems. While there may be other similar products on the market, please note that EP Henry approves and recommends using only those accessory products shown in our catalog.

