

# Anchor Diamond Pro™

Architects, engineers and contractors are choosing Anchor Diamond Pro™ to create flexible, cost-effective solutions for a broad range of large commercial, municipal and residential retaining wall projects.

For contours that shape new environments and colors that blend with the surroundings, the natural choice is Anchor Diamond Pro.



INSIST ON THE BEST.

**EP HENRY**  
FOUNDED 1903

1 800 44 HENRY

[www.ephenry.com](http://www.ephenry.com)




# Anchor Diamond Pro™

All units feature one square foot of wall face combined with a patented rear lip technology to bring simplified construction, improved connection strength and reduced cost to every project. Aesthetically, the natural rock texture and earth tone colors blend easily into any environment. Anchor Diamond Pro can be used with geosynthetic reinforcement for tall wall applications.



No pins. No mortar. No misalignments.  
Patented rear-lip technology makes  
installation quick, efficient and accurate.

## Specifications



**Straight Face\*\***



**Corner**



**Cap**

Nominal Dimensions*	8" x 18" x 12"	8" x 18" x 9"	4" x 18" x 12"
Approx. Weight*	80 lbs.	86 lbs.	60 lbs.
Coverage	1.0 sq. ft.		
Setback/Batter	1" / 7.13°		
Inside Radius	6'		
Outside Radius	4'		

\*\* Bevel Face option available on special request.

**EP HENRY**  
FOUNDED 1903

Anchor Wall Systems products are manufactured by licensed Anchor Wall Systems producers and are backed by a Limited Warranty. For a complete copy of the Anchor Wall Systems Warranty, visit your local EP Henry Authorized Hardscaping Center. Anchor Wall Systems and Diamond Pro are trademarks of Anchor Wall Systems, Inc. Diamond Pro blocks are sold only by licensed Anchor Wall Systems producers and are protected by U.S. patent nos. 5,294,216, 6,142,713, 6,183,168, 6,312,197. Other U.S. and International patents issued and pending.