



## ECO-STRIPPER

FOR PAVERS AND CONCRETE

(60201004 / 18.93 L (5 gal. ))

### UPDATE

---

March 30, 2018

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: [techniseal.com](http://techniseal.com)

Canada and U.S.A.: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Pavers, slabs and retaining walls made of concrete
- For horizontal and vertical applications

### PROPERTIES

---

- Removes most stains, sealants and coatings without affecting the surface
- Eco-friendly: Does not damage vegetation or substrate
- Turns into a powder or a thick paste once dry

### DESCRIPTION

---

The ECO-STRIPPER is a cream that removes virtually all stains, sealants and coatings, which can be easily applied on horizontal and vertical surfaces. This green product does not affect the surface or vegetation. ECO-STRIPPER does not damage the substrate (paver, concrete, etc.) and emits a slight citrus scent.

### DIRECTIONS

---

#### BEFORE YOU BEGIN

Wear adequate protective clothing. **ALWAYS TEST** To ensure the results will meet your expectations, always test product on a small hidden area of approximately 26 cm<sup>2</sup> (4 sq. in.) Do not thin or dilute. This product might not work on certain type of coatings. Keep from freezing. Do not use on asphalt.

#### SURFACE PREPARATION

To allow a good contact between the ECO-STRIPPER and the product to be removed, surface should be free of any dry detritus or debris. Without using any water, sweep clean the surface from any dirt, sand, leaves, detritus or debris.

## APPLICATION

**Important:** Surface and joints must be completely dry (24 hours without precipitation). Temperature should be between 10 and 30°C (50 and 85°F) . At a lower or higher temperature, the product's effectiveness will be reduced. Rain or heavy dew should not be forecasted for the next 24 hours.

### Stir product well before use.

Using a semi-soft bristle street broom, apply a generous amount of product on the surface. There must be enough product to make it completely opaque. Let sit for 8 to 24 hours. Product is dry when it turns from a liquid to a thick paste or powder.

Once product has completely dried, sweep up with a broom and dispose of the residue using the ECO-STRIPPER container. Using a pressure washer (2000 to 2500 psi) with a recommended tip (do not use zero degree or rotating tips), rinse surface in order to completely remove ECO-STRIPPER residue. The use of hot water will make the stripping easier. Let surface dry. Repeat if necessary.

**Note:** Surface may still appear dark immediately after powder has been swept up; this is not remaining sealant, but rather a natural solvent trapped in the pores, which should evaporate within a few hours or days.

**Tool clean-up:** Use water and soap.

## STORAGE

Store in a cool and dry place, in original container.

## COVERAGE

18.93 L (5 gal.) strip up to 19 m<sup>2</sup> (200 sq. ft.)

## PACKAGING

Product code	Size	Units per box	Units per pallet
60201004 (291-596)	18.93 L / 5 gal.	—	36

## WARNING

**KEEP OUT OF THE REACH OF CHILDREN.** Use only with adequate ventilation. Do not breathe vapor or mist. Do not swallow. Do not get in eyes or on skin or clothing. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. **FIRST AID: Contains:** (R)-p-mentha-1,8-diene; N-methyl-2-pyrrolidone; Isotridecanol, ethoxylated; tetrasodium ethylene diamine tetraacetate; Silicic acid, sodium salt. **Eye contact:** Call physician immediately. Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. **Skin contact:** In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse. **Inhalation:** Call physician immediately. Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. **Ingestion:** Call physician immediately. Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Calculated VOC ≤ 40%

## SHIPPING

---

### Land and sea

#### Land

Not regulated

#### Sea

UN3082

Environmentally hazardous substance, liquid, N.O.S. ((R)-p-mentha-1,8-diene)

Class: 9

PG: III

## LIMITED WARRANTY

---

Techniseal® warrants this product against manufacturing defects. As Techniseal® has no control over product use, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim. Notice: user should make sure that this product meets their needs by carrying out a test under anticipated conditions of use on a 4 sq. ft. area. In the event that no test was carried out, the warranty will only apply to 4 sq. ft.